

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 7/50		A1	(11) International Publication Number: WO 98/26603
			(43) International Publication Date: 18 June 1998 (18.06.98)
(21) International Application Number: PCT/FI97/00763 (22) International Filing Date: 8 December 1997 (08.12.97) (30) Priority Data: 60/032,806 9 December 1996 (09.12.96) US (71) Applicant (for all designated States except US): TELECOM FINLAND OY [FI/FI]; Sturenkatu 16, FIN-00510 Helsinki (FI). (72) Inventor; and (75) Inventor/Applicant (for US only): BJÖRKLUND, Dan [FI/FI]; Mariarannankatu 74, FIN-64260 Kaskinen (FI). (74) Agent: PAPULA REIN LAHTELA OY; Fredrikinkatu 61 A, P.O. Box 981, FIN-00101 Helsinki (FI).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: METHOD FOR THE TRANSMISSION OF VIDEO IMAGES

(57) Abstract

The present invention relates to a method for transmitting video images over a data communication network, in which method the video image is encoded at the sending end, transmitted, and decoded at the receiving end. For each block, the difference between successive blocks is transmitted if the block difference exceeds a predetermined threshold.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD FOR THE TRANSMISSION OF VIDEO IMAGES

The present invention relates to a method as defined in the preamble of claim 1 for transmitting video images in a data communication network, preferably a narrow-band data communication network, such as a GSM network.

In prior art, several methods for the transmission of video images in a data communication network are known. A feature typical of these methods is that the image is compressed in some way before transmission to allow faster transmission. Among the prior-art compression methods are e.g. MPEG (Moving Pictures Experts Group), and H.261 and H.263 standardized by ITU (International Telecommunication Union, ITU). The prior-art compression methods are characterized in that, instead of transmitting complete frames, only the differences between successive frames are transmitted. Moreover, predictive coding is used to reduce temporal redundancy, and modification coding to reduce spatial redundancy.

A problem with the prior-art methods is that they apply compression to entire frames and transmit all differences between successive frames. Consequently, the amount of data to be transmitted remains too high for the needs of narrow-band data communication networks. For example, if an MPEG-compressed video image with a resolution of 388*288 is transmitted over a GSM network, the transmission of a single frame may take as long as 15 seconds.

The object of the present invention is to present a new method that eliminates the above-mentioned drawbacks.

A specific object of the invention is to produce a method for processing a video image so that the image can be readily transmitted even in a narrow-band data communication network, such as a GSM network.

As for the features characteristic of the

present invention, reference is made to the claims.

In the method of the present invention for the transmission of video images over a data communication network, the video image is encoded at the sending end, transmitted, and decoded at the receiving end. The equipment at the sending end comprises a reference memory, in which the first frame of the video image is stored. Next, the first frame is compressed and transmitted. At the receiving end, the frame is stored in an image memory. The first frame stored in the reference memory and the next frame in sequence are divided into blocks. Mutually corresponding blocks of the frames are compared with each other to determine a block difference. If the block difference exceeds a specified threshold, then the difference between the blocks is compressed and transmitted. In addition, the block is stored in the reference memory. At the receiving end, the difference is integrated into the image to be presented.

In an embodiment of the method, the frame is divided into blocks having the size of 8*8 pixels.

In an embodiment of the method, the block difference is determined by comparing some of the mutually corresponding pixels contained in blocks corresponding to each other and calculating the number of pixels differing from each other.

In an embodiment of the method, the comparison of pixels is performed using some of the bits indicating pixel value.

In an embodiment of the method, the comparison of pixels is performed based on the luminance component of the pixels.

In an embodiment of the method, a predetermined part of each frame is transmitted and integrated into the image to be presented.

In an embodiment of the method, the compression method used is the JPEG (Joint Photographic Ex-

perts Group, JPEG) method.

As compared with prior art, the present invention has the advantage that it allows a considerable reduction in the amount of data to be transmitted, as the frames are divided into blocks and the difference between blocks corresponding to each other is only transmitted if the block difference is sufficiently large. This makes it possible to transmit video images in a narrow-band network as well. The method is particularly well suited for the transmission of video images obtained from a mainly stationary camera, such as a monitoring camera.

In the following, the invention will be described in detail by the aid of an application example by referring to the attached drawing, in which

Fig. 1 presents a block diagram of the method of the invention;

Fig. 2 presents a hardware assembly implementing the method of the invention; and

Fig. 3 presents an example of data flow transmitted by the method of the invention.

Fig. 1 is a block diagram presenting an example of the method of the invention. The parameter Y_p , which indicates the value of the Y co-ordinate, is set to zero. The first frame of the video image is grabbed and stored in the reference memory. The frame is compressed by the JPEG method and transmitted. At the receiving end, the frame is decompressed, stored in the image memory and presented. The next frame is then grabbed and compared block by block with the first frame. The frames are divided into blocks of 8*8 pixels. In blocks corresponding to each other, the luminance component of every second pixel is compared using five most significant bits. If the absolute difference is larger than two, then the block difference value is increased by one. If a block difference value exceeding 14 is obtained, then the difference between

the blocks being compared is large enough to be transmitted. In this case, the difference between the blocks is calculated, compressed by the JPEG method and transmitted together with position data. In addition, the block under processing is stored in the reference memory. Further, a predetermined part of each frame is transmitted. The size of this part is $x\text{-resolution} * 8$ pixels. The position of the predetermined part is shifted by eight pixels downwards between successive frames, in other words the value of the parameter Y_p is increased by eight for each frame until it reaches the $y\text{-resolution}$ value, whereupon the parameter Y_p is reset to zero.

Fig. 2 presents an example of a hardware assembly implementing the method of the invention. Connected to a television camera, such as a monitoring camera 1, is a device 2 that grabs the frames for processing. The device 2 is further connected to a central processing unit 3, which takes care of image processing at the sending end. The central processing unit 3 communicates with a reference memory 4, which is used for the determination of block difference. The central processing unit 6 at the receiving end decodes the received data. Connected to the central processing unit 6 is an image memory 5, which is used to store the image to be presented. Moreover, the central processing unit 6 is connected to a display unit 7 used to present the image.

Fig. 3 presents an example of the data flow to be transmitted. The frame in the example comprises three blocks whose block differences have been found to be large enough to make it necessary to transmit the difference between successive blocks. These differences make up 192 bytes of data, which is compressed by the JPEG method to 5 bytes. In addition to the data contained in each block, the data transmitted comprises a step number δ , which indicates the position

of each block relative to the beginning of the frame and whose value is determined as follows: 0 -> beginning of frame, 1 -> removed by 8 pixels, 255 -> removed by $8 \cdot 255$ pixels from the beginning.

5 The invention is not limited to the examples of its embodiments described above, but instead many variations are possible within the framework of the inventive idea defined by the claims.

CLAIMS

1. Method for transmitting video images in a data communication network, in which method the video image is encoded at the sending end, transmitted, and
5 decoded at the receiving end, characterized in that

- the first frame is stored in a reference memory provided at the sending end;

- the first frame is compressed and transmitted,
10 whereupon it is stored in an image memory at the receiving end;

- the first frame stored in the reference memory is divided into blocks;

- the next block in sequence is divided into
15 blocks;

- frame blocks corresponding to each other are compared to determine a block difference;

- if the block difference exceeds a predetermined threshold, then the difference between the blocks is
20 compressed and transmitted and the block is stored in the reference memory; and

- the difference is integrated into the image to be presented at the receiving end.

2. Method as defined in claim 1, characterized
25 in that the frame is divided into blocks of 8*8 pixels.

3. Method as defined in claim 1 or 2, characterized in that the block difference is determined by comparing some of the mutually corresponding pixels contained in blocks corresponding to each
30 other and calculating the number of pixels differing from each other.

4. Method as defined in any one of the preceding claims 1 - 3, characterized in that the
35 comparison of pixels is performed using some of the bits indicating pixel value.

5. Method as defined in any one of the preceding claims 1 - 4, characterized in that the comparison of pixels is performed based on the luminance component.

5 6. Method as defined in any one of the preceding claims 1 - 5, characterized in that a predetermined part of each frame is transmitted and integrated into the image to be presented.

10 7. Method as defined in any one of the preceding claims 1 - 6, characterized in that the compression method used is the JPEG method.

1/2




Fig. 1

2/2





Fig. 2



Δ is a step number indicating block position

Fig. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 97/00763

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04N 7/50

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP 7067105 A (SONY CORP.), 10 March 1995 (10.03.95), abstract, see the figures -----	1-7

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 May 1998

Date of mailing of the international search report

28-05-1998

Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

Bengt Romedahl
 Telephone No. +46 8 782 25 00

Information on patent family members

International application No.

PCT/FI 97/00763

Form PCT/ISA/210 (patent family annex) (July 1992)